

D-mig 230 AC - 420S



- MIG/MAG - NO GAS
- TRADITIONAL 1PH


Travail léger
Trabajo liviano
Entretien
Mantenimiento
Menuiserie légère
Carpintería ligera



MADE IN SAN MARINO

		D-mig 230 AC	D-mig 420S
Tension d'alimentation - Tensión de red: 50/60Hz		1 ~ 230V	
Puissance consommée - Consumo energía: 60% / Max		Min. 1,0 / Max 1,8 kW	1,8 / 4,3 kW
Fusible - Fusible		16A	
Rendement - Eficiencia		> 80%	< 80%
Champ de réglage - Campo de regulación		NO GAS	MIG MAG
Positions de soudage - Posiciones de soldadura		90 - 130A	35 - 200A
Facteur de marche - Servicio (40°C EN 60974-1)		2	6
Tension à vide - Tensión en vacío		80A - 20%	165A - 15%
		40A - 90%	80A - 60%
		18 - 22V	29 - 52V
MIG - NO GAS Fil Ø mm Hilo Ø mm	Acier - Acero	-	0,6 - 0,8 - 1,0
	Acier inox - Acero inox	-	0,8
	Al.Mg - Al.Si	-	0,8 - 1,0
	Fourré - con alma FCAW-S	0,9	-
	Bobines - Bobinas Ø mm	100	200 - 300
Ventilé - Ventilada		-	•
Poids - Peso ≈		13,3 kg	41 kg
Dimensions - Dimensiones		330 x 185 x 320 mm	705 x 412 x 465 mm
Code - Código		241300	255000

D-mig 230AC: Accessoires fournis - Accesorios suministrados



D-mig 420 S: Accessoires fournis - Accesorios suministrados



deca@decaweld.com - www.decaweld.com