

EasyJob 220 - 221XL

LABIT
EN

- MULTIPROCESS: MIG/MAG - NO GAS - MMA - TIG
- SYNERGIC
- INVERTER

Manutenzione
Maintenance
Carpenteria leggera
Light carpentry




Queste saldatrici monofase inverter sono perfette per qualsiasi garage e officina ben attrezzata grazie alle loro proprietà di saldatura multiprocesso. Sono le saldatrici ideali per l'artigiano professionista che ha bisogno di vari processi di saldatura per le piccole riparazioni all'aperto e al chiuso. Estremamente compatte, sono disponibili in versione per alloggiare bobine di filo da 200mm oppure 300mm.

- Saldatura: MIG/MAG, FLUX, MMA e TIG Lift
- DC Sinergica. Tutti i parametri principali di saldatura sono collegati e agiscono in maniera combinata.
- Saldobrasatura MIG per acciaio galvanizzato.
- Inversione della polarità: da positiva a negativa e viceversa per saldare con fili animati.
- Pannello di controllo estremamente semplice per un utilizzo in modalità sinergica o manuale.
- Aggiornamento software tramite SD-Card.
- Pacchetto programmi standard di oltre 20 programmi per acciaio dolce, inox, alluminio.

These single-phase inverter welding machines are excellent for any garage and well-equipped workshop given their multi-process welding properties. They are the ideal welding machines for the professional craftsman, who needs different welding processes for minor repairs indoors as well as outdoors.

Extremely compact, they are available in 2 versions accommodating for 200mm or 300mm wire spools.

- Welding processes: MIG/MAG, FLUX, MMA, TIG Lift
- Synergic DC. All the primary welding parameters are linked and work together.
- MIG brazing process for galvanised steel.
- Polarity reverse: from positive to negative and viceversa for welding with flux cored wires.
- Extremely simple panel control for synergic or manual welding.
- Software update via SD-Card.
- Standard package of 20 welding programs for mild steel, stainless steel and aluminum.



Easyjob

Traino 2 rulli
2 Rolls feeder
D.30mm





MADE IN SAN MARINO



EASYJOB 220 LAB

EASYJOB 221XL LAB

Tensione di rete - Input voltage: 50/60Hz		1 ~ 230V +/- 30%			
Potenza assorbita - Absorbed power: 60% / Max		2,8 / 4,5 kW			
Fusibile - Fuse		16A			
Generatore - Generator: Min		7 kW			
		MIG / TIG	MMA	MIG / TIG	MMA
Campo di regolazione - Welding current		10 - 200A	10 - 160A	10 - 200A	10 - 160A
Servizio - Duty cycle (40°C EN 60974-1)		180A - 25%	150A - 25%	180A - 25%	150A - 25%
		100A - 60%	100A - 60%	100A - 60%	100A - 60%
Tensione a vuoto - Open circuit voltage		86V			
MIG	Filo ø mm Wires ø mm	Acciaio - Steel	0,6 - 0,8 - 1,0		
		Inox - Stainless steel	0,8 - 1,0		
		Al.Mg 5	0,8 - 1,0 - 1,2		
		Al.Si 5	1,0 - 1,2		
		Cu.Si 3 / Cu.Al 8	0,8 - 1,0 - 1,2		
		No gas - Flux cored (FCAWS)	0,8 - 0,9 - 1,2		
		Bobina ø mm - Wire spool ø mm	100 - 200	200 - 300	
	Trainafile - Wire feeder		2 rulli - 2 rolls (ø 30mm)		
	Cambio polarità - Reversed polarity		•		
	Amperometro Voltmetro - Ammeter Voltmeter		•		
	Saldatura sinergica - Synergic welding		•		
	Hot start		Regolabile - Adjustable		
Induttanza - Inductance		Regolabile - Adjustable			
Burn back		Regolabile - Adjustable			
MMA	Elettrodi - Electrodes: ø mm	Rutile / basico - Rutile / basic	1,6 - 4,0		
	Hot start / Arc force		Regolabili - Adjustables		
	Anti-sticking		•		
TIG	Innesco arco - Arc striking		LIFT		
	Anti-sticking		•		
	Slope Down		Regolabile - Adjustable		
Utilizzo con generatore - Suitable for generator		•			
Connessioni in uscita - Output connections		Euro / DX 25 mmq			
Peso - Weight ≈		11 kg		13 kg	
Dimensioni - Dimensions		500 x 228 x 415 mm		556 x 268 x 438 mm	
Codice - Code		246000		246100	

Accessori in dotazione - Supplied accessories

 DE M15A - 3m: (Ugello - Tip 0,8mm) +  ■ Fe 0,6 / 0,8mm +  2,7m (16mmq) +  Gas 1,5m