

- MMA
- TRADITIONAL 1PH

Travail léger
Trabajo liviano
Menuiserie légère
Carpintería ligera
Chantier de construction
Sitio de construcción



MADE IN SAN MARINO

	GLOBUS 3.0	GLOBUS 4.0	GLOBUS 5.0 D
Tension d'alimentation - Tensión de red: 50/60Hz	1 ~ 230V		1 ~ 230/400V
Potenza assorbita - Absorbed power: Min / Max	2,0 - 4,0 kW	2,0 - 5,0 kW	2,0 - 6,0 kW
Fusible - Fusible	16A	20A	25/20A
Rendement - Eficiencia	< 80%		
	MMA AC		
Champ de réglage - Campo de regulación	44 - 140A	44 - 160A	30 - 200A
Tension à vide - Tensión en vacío	43 - 49V		41 - 50V
Électrodes -Electrodos: ø mm Rutile - Rutilo	1,6 - 3,2	1,6 - 4,0	1,6 - 5,0
Connexion de sortie - Conexiones en salida	Cavi Câbles directs - Cables directos cables		DX 25 mmq
Ventilé - Ventilada	•		
Protection thermostatique - Protección termostática	•		
Poids - Peso ≈	13,9 kg	15,6 kg	19,7 kg
Dimensions - Dimensiones	380 x 208 x 280 mm		570 x 320 x 350 mm
Code - Código	204500	204700	203700

GLOBUS 3.0 e 4.0 Accessoires fournis - Accesorios suministrados

