

- MMA
- TRADITIONAL 1PH

Utilizzo leggero
Light duty
Carpenteria leggera
Light carpentry
Cantiere edile
Construction site



MADE IN SAN MARINO

	GLOBUS 3.0	GLOBUS 4.0	GLOBUS 5.0 D
Tensione di rete - Input voltage: 50/60Hz	1 ~ 230V		1 ~ 230/400V
Potenza assorbita - Absorbed power: Min / Max	2,0 - 4,0 kW	2,0 - 5,0 kW	2,0 - 6,0 kW
Fusibile - Fuse	16A	20A	25/20A
Rendimento - Efficiency	< 80%		
	MMA AC		
Campo di regolazione - Welding current	44 - 140A	44 - 160A	30 - 200A
Tensione a vuoto - Open circuit voltage	43 - 49V		41 - 50V
Elettrodi - Electrodes: Ø mm	Rutile		
	1,6 - 3,2	1,6 - 4,0	1,6 - 5,0
Connessioni in uscita - Output connections	Cavi diretti - Direct cables		DX 25 mmq
Ventilata - Fan cooled	•		
Protezione termostatica - Thermostatic Protection	•		
Peso - Weight ≈	13,9 kg	15,6 kg	19,7 kg
Dimensioni - Dimensions	380 x 208 x 280 mm		570 x 320 x 350 mm
Codice - Code	204500	204700	203700

GLOBUS 3.0 e 4.0 Accessori in dotazione - Supplied accessories

