


- MULTIPROCESS: MIG/MAG - NO GAS - MMA - TIG
- SYNERGIC PULSE
- INVERTER

Manutenzione
Maintenance
Carpenteria leggera
Light carpentry
Autoriparazioni
Collision repair



Supporto torcia
Torch holder

Ruote industriali
Heavy duty wheels

Vano porta attrezzi
Tools compartment

Multilingua / Multilanguage




Generatore multifunzione top di gamma studiato per la saldatura professionale e saldobrasatura di acciaio ad alta resistenza, acciaio dolce, inossidabile ed alluminio.


- Saldatura: MIG/MAG, FLUX, MMA e TIG Lift
- Pannello di controllo grafico a colori con due modalità di utilizzo: semplice od avanzata.
- DC Sinergica. Tutti i principali parametri di saldatura sono collegati e agiscono in maniera combinata.
- MIG pulsato e doppio pulsato per risultati eccezionali su alluminio di basso spessore ed inox.
- Saldobrasatura MIG per acciaio galvanizzato.
- Inversione della polarità: per saldare con fili animati.
- Pacchetto programmi standard per oltre 20 tipologie di materiale, diametro e gas.
- Memoria digitale per salvare le impostazioni preferite.
- Aggiornamento software tramite SD-Card.

Top-class multiprocess welding machine for professional welding and MIG brazing of high-tensile steel, mild steel, stainless steel and aluminum.

- Welding processes: MIG/MAG, FLUX, MMA, TIG Lift.
- Multicolor graphic display with 2 modes: basic or advanced.
- Synergic DC. All the primary welding parameters are linked and work together.
- Pulse MIG and double pulse MIG to achieve excellent results on welding low thickness aluminum and stainless steel.
- MIG brazing process for galvanised steel.
- Polarity reversal: for welding with flux cored wires.
- Standard package of 20+ types of material, wire diameter and gas.
- Digital memory: to save one's favourite welding settings.
- Software update via SD-Card.



Cruscotto saldatura MIG sinergica
Synergic MIG welding dashboard



Regolazione della sinergia MIG
MIG synergy setting



Job 522 PD

Traino 4 rulli
4 Rolls feeder
D.37mm



MADE IN SAN MARINO



JOB 522 PD LAB

Tensione di rete - Input voltage: 50/60Hz		1 ~ 230V +/- 15%		
Potenza assorbita - Absorbed power: 60% / Max		3,3 / 6,3 kW		
Fusibile - Fuse		25A		
Generatore - Generator: Min		9 kW		
	MIG / TIG		MMA	
	10 - 220A		10 - 160A	
	220A - 20%	160A - 30%		
	140A - 60%	130A - 60%		
	Tensione a vuoto - Open circuit voltage		88V	
MIG	Filo ø mm Wires ø mm	Acciaio - Steel	0,6 - 0,8 - 1,0	
		Inox - Stainless steel	0,8 - 1,0	
		Al.Mg 5	0,8 - 1,0 - 1,2	
		Al.Si 5	1,0 - 1,2	
		Cu.Si 3 / Cu.Al 8	0,8 - 1,0 - 1,2	
		Animato - Flux cored FCAW-S	0,8 - 0,9 - 1,2	
		Bobina ø mm - Wire spool ø mm	200 - 300	
	Trainafilo - Wire feeder		4 rulli - 4 rolls (ø 37mm)	
	Cambio polarità - Reversed polarity		•	
	Amperometro Voltmetro - Ammeter Voltmeter		•	
	Caricamento filo, Test gas - Wire loading, Gas test		•	
	Modo pulsante torcia - Torch trigger mode		2T / 4T / Spot / Stitch	
	Saldatura sinergica - Synergic welding		•	
	Pulsato, doppio pulsato - Pulse, double pulse		•	
	Pre-gas, Accostamento filo, Hot start, - Pre-gas, Approach speed, Hot start		Regolabili - Adjustables	
	Induttanza - Inductance		Regolabile - Adjustable	
	Post gas, Burn back - Post flow, Burn back		Regolabili - Adjustables	
Memoria programmi utente - User job saving		128		
MMA	Elettrodi - Electrodes: ø mm	Rutile / basico - Rutile / basic	1,6 - 4,0	
	Hot start / Arc force		Regolabili - Adjustables	
	Anti-sticking		•	
TIG	Innesco arco - Arc striking		LIFT	
	Anti-sticking		•	
	Slope Down		Regolabile - Adjustable	
	Utilizzo con generatore - Suitable for generator		•	
	Connessioni in uscita - Output connections		Euro / DX 25 mmq	
	Peso - Weight ≈		30 kg	
	Dimensioni - Dimensions		777 x 407 x 792 mm	
	Codice - Code		250500	

Accessori in dotazione - Supplied accessories:



DE M15A - 3m (Ugello - Tip 0,8mm)



■ Fe 0,6 / 0,8mm



2,7m (16mmq)



Gas 1,5m