

Entretien
Mantenimiento
Menuiserie légère
Carpintería ligera
Carrosserie
Carrocería
Soudage de précision
Soldadura de precisión

Mastrotiq 218 dc



MADE IN SAN MARINO



MASTROTIG 216 LAB

MASTROTIG 218 LAB

Tension d'alimentation - Tensión de red: 50/60Hz		1 ~ 230V +/- 15%				
Potenza assorbita- Absorbed power: 60% / Max		2 / 4 kW		3,3 / 5,7 kW		
Fusible - Fusible		16A		25A		
Générateur - Generator: Min.		6 kW		9 kW		
		TIG AC/DC	MMA	TIG DC	MMA	
	Champ de réglage - Campo de regulación	5 - 160A	20 - 130A	5 - 200A	20 - 180A	
	Facteur de marche - Servicio (40°C EN 60974-1)	160A - 20%	130A - 25%	200A - 30%	180A - 30%	
		85A - 60%	80A - 60%	140A - 60%	130A - 60%	
	Tension à vide - Tensión en vacío	105V		90V		
	Électrodes: ø mm - Electrodo: ø mm	1,0 - 3,2		1,0 - 4,0		
	Gestions de gâchette - Gestiones del gatillo	2T / 4T / SPOT				
	Amorçage de l'arc - Cebado de arco	HF - LIFT				
	Pré-Gaz / Slope Up - Pre-Flujo / Slope Up	Réglables - Ajustables				
	Pulsé - Pulsado	AC 0,2 - 2,0 Hz DC 0,2 - 250 Hz		----- DC 0,2 - 250 Hz		
TIG	DC / EasyPulse - DC EasyPulse	•				
	DC Bilevel	•				
	Slope Down / Post-gas - Slope Down / Post-Flujo	Réglable - Ajustable				
	AC Pulsé- AC pulsado	10 - 200 Hz		---		
	AC-Easy - AC-Easy	•		-		
	AC Balance	•		-		
	Mémoire de programmes - Memoria de programas	9				
	MMA	Électrodes: ø mm	Rutile - Rutilo	1,6 - 3,2		1,6 - 5,0
		Electrodos: ø mm	Basique - Básico	2,0 - 3,2		2,0 - 4,0
	Hot start / Arc force		Réglables - Ajustables			
Anti-collage - Anti-adherencia		•				
	Télécommande - Control remoto		Optional			
	Connexion de sortie - Conexiones en salida		DX 25 mmq			
	Poids - Peso ≈		12 kg		9 kg	
	Dimensions - Dimensiones		418 x 200 x 344 mm		430 x 200 x 344 mm	
	Code - Código		284200		284100	

Accessoires fournis - Accesorios suministrados:

Mastrotig 216:  TG17V - 4m (Ø 1,6 WR2 Acier - Acero) (Ø 1,6 WP alu)

Mastrotig 218:  TG17V - 4m (Ø 1,6 WR2 Acier - Acero)



2,7m (16 mmq)

2,7m (16 mmq)



Gas 1,5m

Gas 1,5m